

PAPER REF: 7090

IDENTIFICATION OF HYSTERICALLY DEGRADING STRUCTURES USING THE BOUC-WEN-BABER-NOORI (BWBN) MODEL

Ying Zhao¹, Mohammad Noori^{1,2(*)}, Wael Altabay^{1,3}

¹International Institute for Urban Systems Engineering, Southeast University, Nanjing, China

²Mechanical Engineering Dept., California Polytechnic State University, San Luis Obispo, California, USA

³Department of Mechanical Engineering, Faculty of Engineering, Alexandria University, Alexandria, Egypt

(*)Email: contact@mohammadnoori.com

ABSTRACT

Structural control and health monitoring scheme are playing a key role not only to enhance life safety for infrastructure systems but also to optimally minimize the life cycle cost and maximize the performance through the full life cycle design under natural disasters. In this paper, first the characteristics of Bouc-Wen-Baber-Noori model are presented, and subsequently we analyze a three story shear structure subjected to sine wave by using Intelligent Parameter Varying approach, Genetic Algorithm and Transitional Markov Chain Monte Carlo method. Correlation study is made to compare the system identification results.

Keywords: hysteretic behavior, BWBN model, Genetic algorithm, transitional MCMC.

INTRODUCTION

Under cyclic loading, mechanical or structural systems may dissipate considerable energy through hysteretic behavior. A few examples of Bouc-Wen-Baber-Noori (BWBN) general hysteresis models have been studied (Dobson, 1997; Zhang, 2002). An intelligent parameter varying approach (IPV) proposed by (Saadat, 2007) to overcome the limitations of traditional system identification techniques is utilized herein to identify the system parameters of a BWBN system. A shear structure with BWBN hysteretic restoring force is subjected to ambient sinusoidal wave and the implication of the parameters of the model is carried out.

$$m\ddot{x} + c\dot{x} + R = F(t) \quad (1)$$

$$R = \alpha kx + (1 - \alpha)kz \quad (2)$$

$$\dot{z} = \frac{Ax_1 - v[\beta|x_1||z|^{n-1}z + \gamma x_1|z|^n]}{\eta} \quad (3)$$

$$x_1 = \sqrt{\frac{2}{\pi}} \frac{s}{\sigma} \exp\left[-\frac{x^2}{2\sigma^2}\right] \dot{z} \quad (4)$$

$$\dot{s} = (1 - \alpha)k\dot{x}z \quad (5)$$

$$s = \delta_z s \quad (6)$$

The structure is composed of three lumped mass subsystems, where each subsystem (floor m_i) only moves laterally, and the structural restoring force R_i between the adjacent floors is modeled by incorporating a BWBN hysteresis model. In this study, for system identification, an Intelligent Parameter Varying (IPV) technique, with embedded radial basis function networks are used to estimate the constitutive characteristics of hysteretic restoring forces. This approach is then compared with the results using a genetic algorithm (Charalampakis, 2010), and a Transitional Markov Chain Monte Carlo (TMCM) approach (Zhang, 2001).

RESULTS AND CONCLUSIONS

Due to space limitation only the tables summarizing the correlation coefficient analyses are presented. Table 1 show that the simulated response of the IPV based model approximates the true response of the hysteretic structural system subjected to sinusoid input, and the system identification results show that the correlation coefficients are equal to 1.

Table 1 - Correlation Coefficient Analysis for IPV

CR-t3	CR-t2	CR-t1	CR-x3	CR-x2	CR-x1
1.0000	1.0000	1.0000	1.0000	1.0000	1.0000

The correlation coefficient results using genetic algorithm are shown in Table 2. The results show that the correlation coefficients approach 1, especially for the first floor of the hysteretic structure subjected to sinusoid input.

Table 2 - Correlation Coefficient Analysis

CRt3	CRt2	CRt1	CRx3	CRx2	CRx1
0.9546	0.9770	0.9829	0.9546	0.9770	0.9829

The correlation coefficients for TCMCM using a Bayesian inference framework are shown in Table 3. We can see that the correlation coefficients approach 1 and the system identification result is relatively accurate.

Table 3 - Correlation Coefficient Analysis

CR-t3	CR-t2	CR-t1	CR-x3	CR-x2	CR-x1
0.9925	0.9932	0.9957	0.9925	0.9932	0.9957

ACKNOWLEDGMENTS

This research was supported by International Institute for Urban Systems Engineering, Southeast University, via a grant provided by 1000 program for the recruitment of Global Experts, This support is gratefully appreciated.

REFERENCES

- [1] Dobson S, Noori M, Hou Z, Dimentberg M, Baber T. Modeling and random vibration analysis of SDOF systems with asymmetric hysteresis. *International Journal of Non-Linear Mechanics*. 1997 Jul 31; 32(4), pp. 669-80.
- [2] Zhang H, Foliente GC, Yang Y, Ma F. Parameter identification of inelastic structures under dynamic loads. *Earthquake engineering & structural dynamics*. 2002 May 1; 31(5), pp. 1113-30.
- [3] Saadat S, Buckner GD, Noori MN. Structural system identification and damage detection using the intelligent parameter varying technique: an experimental study. *Structural Health Monitoring*. 2007 Sep 1; 6(3), pp. 231-43.
- [4] Charalampakis AE, Dimou CK. Identification of Bouc-Wen hysteretic systems using particle swarm optimization. *Computers & structures*. 2010 Nov 30; 88(21), pp. 1197-205.
- [5] Zhang BT, Cho DY. System identification using evolutionary Markov chain Monte Carlo. *Journal of Systems Architecture*. 2001 Jul 31; 47(7), pp. 587-99.